



# DECLARATION OF PERFORMANCE

DOP 104 - 0002

10/07/2013 -UK

1. Unique identification code of the product-type:

Marmorette Acoustic 4,0+4,5 mm, Colorette Acoustic 4,0+4,5 mm, Uni Walton Acoustic 4,0+4,5 mm, Granette Acoustic 4,0+4,5mm, Linorette Acoustic 4,0+4,5mm

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

121, 131 4,0mm / 4,5 mm, 101 4,0mm / 4,5 mm, 117 4,0mm / 4,5mm, 124 4,0mm / 4,5mm

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

For use as floor covering in buildings (see EN 14041) according to the manufacturer's specifications.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Armstrong DLW GmbH, Stuttgarter Str. 75, 74321 Bietigheim-Bissingen

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 1

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Name of notified certification body that performed the initial inspection of the manufacturing plant and of factory production control, continuous surveillance, assessment and evaluation of factory production control and issued the certificate of constancy of performance.

MPA notified body no. 0672

901 1347 0082

Notified Body




1658-CPR-3002

certificate of constancy of performance

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

not applicable

9. Declared performance

| Essential characteristics         | Performance   | Harmonised technical specification |
|-----------------------------------|---|------------------------------------|
| Reaction to fire                  |  | EN 14041: 2004/AC:2006             |
| Content of Pentachlorophenol      | NPD   | EN 14041: 2004/AC:2006             |
| Formaldehyd Emissions             |  | EN 14041: 2004/AC:2006             |
| Slip resistance                   |  | EN 14041: 2004/AC:2006             |
| Electrical behavior (dissipative) | NPD   | EN 14041: 2004/AC:2006             |
| Electrical behavior (conductive)  | NPD   | EN 14041: 2004/AC:2006             |
| Electrical behavior (antistatic)  | NPD   | EN 14041: 2004/AC:2006             |
| Thermal conductivity [W/mK]       | 0,17 W(m.K)   | EN 14041: 2004/AC:2006             |
| Water-tightness                   | NPD   | EN 14041: 2004/AC:2006             |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

Signed for and on behalf of the manufacturer by:

Charles Irving-Swift / CEO

(name and function)

Bietigheim-Bissingen, 10.07.2013

(place and date of issue)

(signature)