

## EXPONA CLIC 19dB with PUR surface coating

## EXPONA CLIC 19dB

### 1. GENERAL INFORMATION

Well planned and regular maintenance, tailored to traffic conditions and frequencies, will help keep the EXPONA CLIC 19dB floorcovering in pristine condition. Without regular maintenance, standards of appearance, hygiene and cleanliness, as well as the life expectancy of the floorcovering, will be compromised.

EXPONA CLIC 19dB floor panels incorporates a polyurethane (PUR) surface treatment, which protects the floorcoverings by resisting soiling. This protection facilitates the maintenance and provides the foundation for the ongoing maintenance regime.

### 2. PREVENTATIVE MEASURES

In the initial stages of construction planning, attention should be paid to minimising the amount of dirt and water that can enter the building. To facilitate this we strongly recommend the installation of passive dirt barrier systems in all entrance areas e.g. scraper and moisture mats. The mats should be positioned to ensure that access cannot be gained without walking on them, ideally they should be at least four to six paces wide.

### 3. INITIAL CONSTRUCTION CLEAN

After laying, a final construction cleaning is to be carried out. All contamination and residue caused by production is completely removed here with a neutral or PU cleaner. The surface can be polished if desired with a single-disc machine (at least 400–600 rpm.) through using a white polishing pad, or in the case of strongly structured surfaces, by means of soft brush.

### 4. APPLICATION OF A FLOORDRESSING

It is not necessary to apply such a protection to objectflor floorcoverings with a PUR surface treatment as this treatment will provide permanent protection.

### 5. ROUTINE MAINTENANCE

#### Daily

Mop sweep or vacuum the floor to remove dust and loose dirt. Stubborn marks should be removed using a neutral or a PU cleanser. If required, dry buff with a single-disc machine and a white pad.

#### Damp mop

Thanks to a 2-step mopping system with double wheeled bucket, good cleaning results are obtained.

**Please use cleaning detergents sparingly (wipe with a slightly damp applicator).**

### Spray Cleaning / Burnishing

Burnish the floor by using a rotary machine (at least 400–600 rpm) and clean the floor by additionally using a spray cleaning product. This will add further protection and it will improve the appearance of the floorcovering. Use a clean soft white pad.

### 6. PERIODICALLY

It may become necessary to remove stubborn marks from time to time by using a neutral or a PU detergent according to the manufacturers' instructions.

### 7. REMOVAL OF POLISH

A thorough clean may be necessary from time to time, if ongoing general cleaning is no longer producing a satisfactory result or the surface has been damaged by excessive abrasive wear (soiling with sand/grit, sharp-edged items) on the same sections of the surface.

The floor should then be scrubbed using a mono-pad rotary machine (green pad) or a scrubber and the slurry should be removed completely. Neutralise the floor with clean water. Then re-apply a floor dressing (polish of the polymer dispersion type or of the PU sealing type).

Please heed the recommendations of the cleaning agent manufacturer

### IMPORTANT NOTES

EXPONA CLIC 19dB flooring should be cleaned dry or with a damp cloth/mop.

When selecting cleaning and maintenance products and the mechanics used, ensure that these are adapted to one another and consider the manufacturer's notes.

When using wheeled chairs, double swivel rollers are to be used (soft type). The contact areas of mobile furniture should be equipped with suitable felt or soft plastic bearings.

**For further guidance contact objectflor Customer Technical Support or visit our homepage: [www.objectflor.de](http://www.objectflor.de)**