

| CERTIFICATION AND CLASSIFICATION | | Spark | |
|--------------------------------------|------------------------|----------|---|
| Type of flooring | EN 651 | | Vinyl floor covering |
| CE certification | | | yes |
| Classification | ISO 10874 | | Residential: 34 Commercial: 43 |
| TECHNICAL CHARACTERISTICS | | STANDARD | |
| Extreme protection PUR reinforcement | | | yes |
| Total thickness | ISO 24346 | | 2,00 mm |
| Wear layer thickness | ISO 24340 | | 0,70 mm |
| Total weight | ISO 23997 | | 2,22 kg/m ² |
| Form of delivery - Rolls | ISO 24341 | | 25 lm (15 - 25 lm) x 2 m |
| Wear layer binder content | | | Type 1 |
| TECHNICAL PERFORMANCES | | STANDARD | |
| Dimensional stability | ISO 23999 | | ≤ 0,1% |
| Reaction to fire | ISO 13501-1 | | Bfl - s1; report No: 153/BP/15 |
| Residual indentation | ISO 24343-1 | | ≤ 0,10 mm |
| Impact sound reduction | ISO 717/2 | | 14 dB |
| Underfloor heating | | | Suitable provided that the surface of the subfloor does not exceed 27°C |
| Fungi and bacteria resistance | | | Does not contribute to infection spreading |
| Slip resistance / Ramp test | DIN 51130 | | R 10 |
| Castor chair test | ISO 4918 | | Excellent |
| Light fastness | ISO 105 B02 - Method 3 | | 7/8 |
| Thermal resistance | DIN 52612 | | 0,01 - 0,02 m ² K/W |



| | | |
|--|------------------|---|
| | | Manufactured by: Tarkett D.O.O. Industrijska Zona 14 21400 Bačka Palanka SERBIA |
|--|------------------|---|