Universe

TECHNICAL DATA SHEET

December, 2020

CERTIFICATION AND CLASSIFICATION		Universe
Type of flooring	EN 651	Vinyl floor covering
CE certification		yes
Classification	ISO 10874	Commercial: 34 Industrial: 43

TECHNICAL CHARACTERISTICS	STANDARD	Universe
Extreme protection PUR reinforcement		yes
Total thickness	ISO 24346	2,00 mm
Wear layer thickness	ISO 24340	0,70 mm
Total weight	ISO 23997	2,22 kg/m²
Form of delivery - Rolls	ISO 24341	25 lm (15-25 lm) x 2 m
Wear layer binder content		Type 1

TECHNICAL PERFORMANCES	STANDARD	Universe
Dimensional stability	ISO 23999	≤ 0,1%
Reaction to fire	ISO 13501-1	Bfl - s1 No. 328/BP/20
Residual indentation	ISO 24343-1	≤ 0,1 mm
Impact sound reduction	ISO 717/2	10 dB
Thermal conduction (EN ISO 10456)		0,1-0,2 W/m x K
Underfloor heating		Suitable provided that the surface of the subfloor does not exceed 27°C
Fungi and bacteria resistance		Does not contribute to infection spreading
Slip resistance / Ramp test	DIN 51130	R 10
Castor chair test	ISO 4918	Excellent resistance

EXTREME® PROTECTION innovative floors Tarkett

EMBOSS® EFFECT innovative floors Tarkett

15® YEARS WARRANTY Tarkett

EASY® TO CLEAN Tarkett

EASY® TO INSTALL Tarkett

PHTHALATE FREE Technology

ISO 9001 SGS ISO 14001 SGS ISO 45001 SGS ISO 50001 SGS

CE

EN 14041 : 2004

DS EN 13893 EN 1815 EN 12524

Manufactured by:
Tarkett D.O.O.
Industrijska Zona 14
21400 Bačka Palanka
SERBIA

Tarkett